

**PRECISION RULON FCJ BEARINGS**

FCJ PART NUMBER	BEARING I.D.	BEARING O.D.	LENGTH +/- .0075	PRESS FIT	RECOMMENDED HSG. BORE
FCJ-1620-12P	<u>1.0035</u>	<u>1.2515</u>	1.5000	<u>0.0020</u>	<u>1.2500</u>
	1.0025	1.2505		.00005	1.2495
FCJ-2024-16P -32P	<u>1.2535</u>	<u>1.5015</u>	2.0000	<u>0.0020</u>	<u>1.5000</u>
	1.2525	1.5005	4.0000	0.0005	1.4995
FCJ-2432-18P	<u>1.5035</u>	<u>2.0025</u>	2.2500	<u>0.0025</u>	<u>2.0010</u>
	1.5025	2.0015		0.0005	2.0000
FCJ-3240-24P	<u>2.0040</u>	<u>2.5025</u>	3.0000	<u>0.0025</u>	<u>2.5010</u>
	2.0030	2.5015		0.0005	2.5000
FCJ-4048-30P	<u>2.5045</u>	<u>3.0025</u>	3.7500	<u>0.0025</u>	<u>3.0010</u>
	2.5035	3.0015		0.0005	3.0000
FCJ-4856-32P -48P	<u>3.0030</u>	<u>3.5040</u>	4.0000	<u>0.0050</u>	<u>3.5010</u>
	3.0020	3.5020	6.0000	0.0015	3.4990

Standard lengths shown. Other lengths available upon request.

**These parts are machined by Welker from tubes manufactured by Furon.**

**Shaft recommendations: RB 25 Minimum. 8-16 RMS Steel, Stainless**